

Cámara remota Full HD compatible con NDI |HX

AW-HN38H

Cámara remota Full HD compatible con NDI |HX



KEY FEATURES

- Sensor MOS de tipo 1/2,3
- Zoom óptico 22x, i.Zoom 30x y zoom digital 16x
- Conectividad IP para la interfaz web y el control, además de compatibilidad con PoE+ para control de la cámara, retransmisión en directo y alimentación con un solo cable
- Salida de vídeo HDMI, además de la grabación integrada en USB y tarjetas microSD
- NDI|HX - PoE+ para alimentación, audio/vídeo de muy baja latencia, tally y control con un solo cable

SPECIFICATIONS

Color	Black (K) or White (W)
Sensor	1/2.3 inch MOS
Optical Zoom	22x
i.Zoom	30x
Digital Zoom	16x
FOV (Horizontal)	61.6° (W) - 2.9° (T)
FOV (Vertical)	37.0° (W) - 1.6° (T)
FOV (Diagonal)	68.7° (W) - 3.3° (T)
Focus	Auto / Manual
Horizontal Resolution	1000 Lines
Minimum Illumination	0.35 lx
Gain	0 dB - 48dB
Power	PoE+ or AC
Weight (kg)	Approx. 1.5 kg
Weight (lbs.)	3.30 lbs
Instalación	Tripod, Wall*2, Ceiling
Mount Position	Invertible
Standard Warranty	1 Year

Pan Range	±175 degrees
Tilt Range	-30 to 90°
Pan / Tilt Speed	300°/s (Preset) 90°/s (M)
Operation Noise	NC35 or Less
LAN with built-in NDI HX*1	☑
3G-SDI	-
HD-SDI	-
SD-SDI	-
HDMI	☑
Composite	-
USB	☑
Output Format	1080/59.94p, 1080/29.97p, 1080/59.94i, 1080/29.97PsF, 720/59.94p, 1080/50p, 1080/25p, 1080/50i, 1080/25PsF, 720/50p
Live Production Center (Streaming Switcher/Controller)	AV-HLC100
Wide-Angle Tablet Control	AW-HEA10
IR Remote Control	AW-RM50
Compact Controller	AW-RP50
Full-Size Controller	AW-RP120
Remote Operation Panel	AK-HRP200
Compact Live Switcher	AW-HS50N
IP Live Preview	☑
Simultaneous Multi-Stream	☑
Image Stabilization	Electronic
Night Mode (for IR)	☑
Dynamic Range Stretch (DRS)	☑
Audio Input / Embedding	☑
Color Temperature Adjustment	☑
Presets	Up to 100
microSD Card Recording	☑
High Dynamic Range (HDR)	☑
Fanless Design	☑
ND Filters	-
Genlock	-
Advanced Color Adjustment	-
Digital Noise Reduction (DNR)	☑
Note	*1: This product is compatible with NDI HX technology of NewTek, Inc. *2: With appropriate right angle wall mount, available locally *3: HDMI output only. *4: When either 480/59.94p(i) or 576/50p(i) is selected, the output formats are delivered as follows: P signal for HDMI output and I signal for SDI output.
Peso	3.30 lbs

URL: <https://business.panasonic.es/professional-camera/NDI-PTZ-Camerast/aw-hn38>

CONTACT

Web: <https://business.panasonic.es/professional-camera/contact-us>